

НТ

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	

HT

4" THREE-PHASE ENCAPSULATED SUBMERSIBLE MOTOR (3X380-415V / 50 HZ)

Electric motors from series HT are 2 pole asynchronous three-phase submersible motors designed to operate coupled to hydraulic parts with 4" Nema standard. They are made of materials suitable for contact with water, and cooling and lubrication of the thrust block and bushes are guaranteed by a mixture of water and glycol.

HT motors require a start, operation and protection system. Supply cable connector, removable for quick and easy maintenance.

APPLICATIONS

HT encapsulated water-cooled motors ensure reliable working in 4" or larger diameter wells and are designed to be used for lifting, distribution, and pressurisation of water in water systems. HT motors are equipped with phase separator which ensures optimal operation when the motor is used with frequency inverter.

CHARACTERISTICS OF CONSTRUCTION

- 2 pole asynchronous three-phase encapsulated water-cooled motor.
- Axial and radial water-lubricated bearings allow for maintenance-free operation.
- Hermetically sealed stator by 304L stainless steel flanges, internal and external casings, filled by resin to guarantee optimal cooling capacity of temperature during operation.
- Rotor set on Kingsbury thrust block equipped with carbon clearance ring and oscillating pads in high-strength stainless steel to sustain high axial loads.
- Pre-filled with non-contaminating antifreeze lubricant liquid.
- Sand protection to guarantee optimal operation even with sand in the borehole.
- Removable lead connector to make installation and maintenance easier.
- Supply cable according to drinking water regulations (ACS), available in different lengths.

kW: 0,37 - 3

Voltage range: 3x380-415V / 50Hz

Flange: 4" NEMA standard dimensions

Voltage tolerance 50Hz from nominal: +6% / -10% U_n

Rotation: reversible

Degree of protection: IP 68

Insulation: F

Rated ambient temperature: max. 35° C

Cooling flow: min 8 cm/sec

Maximum starts/h: 150, equally distributed

Mounting: vertical/horizontal

Maximum immersion depth: 300 m

Allowed range of water pH: 6,4 - 8,0

Thrust: 1.500 N, 3.000 N (according to ranges)

Protection requirements: For HT motors an overload protection and a control unit for motor start and run must be installed according to EN 60947-4-1 trip time < 10 sec. at $5xI_N$.

INFORMATION ON A PROPER INSTALLATION

- Before installation, it is necessary to verify technical requirements of the given hydraulic part (thrust, power) to select the correct motor.
- If you are using a generator with an internal combustion engine, it is necessary that the generator's power measured in kW (in continuous delivery) is three times the rated power in kW of the submersible pump.
- We recommend to install a proper cooling jacket in installations bigger than 10 cm, to guarantee the correct motor cooling flow.
- Maximum quantity of suspended sand: 150 g/m³.

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231	Казань (843)206-01-48	Новокузнецк (3843)20-46-81	Смоленск (4812)29-41-54
Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Новосибирск (383)227-86-73	Сочи (862)225-72-31
Астрахань (8512)99-46-04	Калуга (4842)92-23-67	Омск (3812)21-46-40	Ставрополь (8652)20-65-13
Барнаул (3852)73-04-60	Кемерово (3842)65-04-62	Орел (4862)44-53-42	Сургут (3462)77-98-35
Белгород (4722)40-23-64	Киров (8332)68-02-04	Оренбург (3532)37-68-04	Тверь (4822)63-31-35
Брянск (4832)59-03-52	Краснодар (861)203-40-90	Пенза (8412)22-31-16	Томск (3822)98-41-53
Владивосток (423)249-28-31	Красноярск (391)204-63-61	Пермь (342)205-81-47	Тула (4872)74-02-29
Волгоград (844)278-03-48	Курск (4712)77-13-04	Ростов-на-Дону (863)308-18-15	Тюмень (3452)66-21-18
Вологда (8172)26-41-59	Липецк (4742)52-20-81	Рязань (4912)46-61-64	Ульяновск (8422)24-23-59
Воронеж (473)204-51-73	Магнитогорск (3519)55-03-13	Самара (846)206-03-16	Уфа (347)229-48-12
Екатеринбург (343)384-55-89	Москва (495)268-04-70	Санкт-Петербург (812)309-46-40	Хабаровск (4212)92-98-04
Иваново (4932)77-34-06	Мурманск (8152)59-64-93	Саратов (845)249-38-78	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Набережные Челны (8552)20-53-41	Севастополь (8692)22-31-93	Череповец (8202)49-02-64
Иркутск (395)279-98-46	Нижний Новгород (831)429-08-12	Симферополь (3652)67-13-56	Ярославль (4852)69-52-93
Россия (495)268-04-70	Киргизия (996)312-96-26-47	Казахстан (7172)727-132	